

## IN THE CLAIMS

Please amend claims 1-12 as follows:

1. (Currently Amended) A tamper-resistant fault detection ~~processing~~ method for an IC card ~~including performing a symmetric-key encryption process utilizing~~ an information processing device mounted thereon, comprising the steps of:
  - (1) performing a ~~symmetric-key~~ encryption process  $Z = E(M, K)$  in which a secret key  $K$  is to be applied to an input plaintext  $M$ , and ~~[[for]]~~ storing a processing result  $Z$  in a memory in the IC card;
  - (2) performing a corresponding decryption process  $W = D(Z, K)$  for said process result  $Z$  stored on said memory and storing the decryption result  $W$  on the memory;
  - (3) outputting said processing result  $Z$  from said information processing device when said processing result  $W$  coincides with said plaintext  $M$ ; and
  - (4) suppressing the output of said processing result  $Z$  from said information processing device when said processing result  $W$  does not coincide with said plaintext  $M$ .
2. (Currently Amended) ~~[[An]]~~ The encryption processing method of claim 1 wherein said encryption process and said decryption process are executed according to the DES (data encryption standard).
3. (Currently Amended) ~~[[An]]~~ The encryption processing method of claim 1 wherein said information processing device is reset as a control method of suppressing the output of said processing result.
4. (Currently Amended) ~~[[An]]~~ The encryption processing method of claim 1 wherein said information processing device and said memory are respectively an arithmetic processing unit and a storage unit to be mounted on an IC card.

5. (Currently Amended) A tamper-resistant fault detection processing method for an IC card including performing a symmetric-key decryption process utilizing an information processing device mounted thereon, comprising the steps of:
- (1) performing a symmetric-key decryption process  $Z = D(C, K)$  wherein a secret key  $K$  is to be applied to an input ciphertext  $C$ , and storing the processing result  $Z$  on a memory in the IC card;
  - (2) performing a corresponding encryption process  $W = E(Z, K)$  for the processing result  $Z$  stored on said memory, and storing the result  $W$  on the memory;
  - (3) outputting said processing result  $Z$  from said information processing device when said processing result  $W$  coincides with said ciphertext  $C$ ; and
  - (4) suppressing the output of said processing result  $Z$  from said information processing device when said processing result  $W$  does not coincide with said ciphertext  $C$ .
6. (Currently Amended) ~~[[A]]~~ The decryption processing method of claim 5 wherein said encryption process and said decryption process are executed according to the DES (data encryption standard).
7. (Currently Amended) ~~An encryption~~ The decryption processing method of claim 5 wherein said information processing device is reset as a method of suppressing the output of said processing result.
8. (Currently Amended) ~~An encryption~~ The decryption processing method of claim 5 wherein said information processing device and said memory are respectively an arithmetic processing unit and a storage unit ~~to be mounted on an IC card~~.
9. (Currently Amended) A tamper-resistant fault detection processing method for an IC card including performing an asymmetric-key encryption process utilizing an information processing device mounted thereon, comprising the steps of:

(1) performing an asymmetric-key decryption process  $Z = D(C, X, J)$  wherein a secret key X and a ~~public key information J~~ are is to be applied to an input ciphertext C and storing the result Z in a memory in the IC card;

(2) performing a corresponding encryption process  $W = E(Z, J)$ , wherein a public key J is to be applied to ~~[[for]]~~ the result Z on said memory and storing said result W on the memory;

(3) outputting the processing result Z from said information processing device when said processing result W coincides with said ciphertext C; and

(4) suppressing the output of the processing result Z from said information processing device when said processing result W does not coincide with the ciphertext C.

10. (Currently Amended) ~~An encryption~~ The decryption processing method of claim 9 wherein said encryption process and said decryption process are executed according to RSA cryptosystem.
11. (Currently Amended) ~~An encryption~~ The decryption processing method of claim 9 wherein said information processing device is reset as a method of suppressing the output of said processing result.
12. (Currently Amended) ~~An encryption~~ The decryption processing method of claim 9 wherein said information processing device and said memory apparatus are respectively an arithmetic processing unit and a storage unit to be mounted on an IC card.